



Reinforced Concrete Maintenance Holes

SIZE (mm)	DESCRIPTION	HEIGHT (m)	APPROX. MASS	PRICE \$
1200	taper top c/w steps	1.320	1905 kg/pc	723.40 ea
1200	flat cap	0.305	715 kg/pc	412.10 ea
1200	riser c/w steps	0.305 to 1.829	1324 kg/m	527.10 /m
1200	monolithic base c/w steps	0.914	1960 kg/pc	950.90 ea
1200	base slab	0.203	780 kg/pc	412.10 ea
1200	safety grate supplied & installed			987.60 ea
1500	flat cap	0.430	1810 kg/pc	821.20 ea
1500 to 1200	transition c/w steps	0.610	1678 kg/pc	821.20 ea
1500	riser c/w steps	3.05 to 2.438	1927 kg/m	798.80 /m
1500	monolithic base c/w steps	1.067	3315 kg/pc	1,916.30 ea
1500	base slab	0.305	1770 kg/pc	821.20 ea
1500	safety grate supplied & installed			1,390.60 ea
1800	flat cap	0.430	2720 kg/pc	1,107.40 ea
1800 to 1200	transition c/w steps	0.610	2400 kg/pc	1,107.40 ea
1800	riser c/w steps	0.610 to 2.438	2756 kg/m	1,135.80 /m
1800	base slab	0.305	2630 kg/pc	1,107.40 ea
1800	safety grate supplied & installed			1,804.50 ea
2400	flat cap	0.430	4980 kg/pc	2,194.40 ea
2400 to 1200	transition slab c/w steps	0.430	4210 kg/pc	2,194.40 ea
2400	riser c/w steps	0.610 to 2.438	4598 kg/m	2,025.10 /m
2400	base slab	0.305	4620 kg/pc	2,194.40 ea
2400	safety grate supplied & installed			2,821.70 ea
3000	flat cap	0.450	7847 kg/pc	3,695.50 ea
3000 to 1200	transition slab c/w steps	0.450	7258 kg/pc	3,695.50 ea
3000	riser c/w steps	0.610 to 2.438	7043 kg/m	3,168.30 /m
3000	base slab	0.305	8225 kg/pc	3,695.50 ea
3000	safety grate supplied & installed			on request

IMPORTANT: 2400mm and 3000mm MAINTENANCE HOLES TO BE OFF-LOADED BY CONTRACTOR.

NOTE:

- 1) Self lubricating gaskets included in price.
- 2) Prices on product manufactured to OPSD 700 series and OPSD 1000 series.
- 3) Install outlet pipe in centre of precast outlet opening.
- 4) Standard steps conform to OPSD 405.010.
- 5) Solid aluminum steps available upon request.