



**\*NOTE: MAXIMUM OF (2) OPENINGS PERMITTED**

ALL DIMENSIONS ARE IN mm  
DRAWINGS ARE NOT TO SCALE  
ALL VIEW AS Poured UNLESS SPECIFIED  
WWF SHEETS TO CSA ASTM A1064  
WWF Fy = 485MPa (Deformed) 450MPa (Smooth)  
REINFORCING TO CSA G.30.18 GRADE 400W

CCP DESIGN REFERENCE: 16-041  
MIN. CONC STRENGTH 40MPa  
DESIGN ACCORDING TO CSA S6-14  
EARTH COVER = 0 - 0.6m  
TOLERANCE TO CSA A23.4  
MAX OF (2) OPENINGS PERMITTED.  
MAX BURIED DEPTH = 4.0m (TO  
BOTTOM OF BASE SLAB)

**CON CAST PIPE (CCP) STANDARD DRAWING**

STD.	-	DOC ID	CX07
<b>SUPER CATCH BASIN 1800 X 900 STACK DRAWING</b>			
0	INITIAL RELEASE	AP	18/OCT/16
REV.	DESCRIPTION	ENG.	DATE
		DRAWN BY	CHECKED BY
		SM	AP/SW
		DATE	FILE
		18/OCT/2016	SuperCB-STACK
		PAGE	1 OF 1