

## Concrete Pipe

### Approximate Mass & Dimensions

| INSIDE DIA.<br>(mm) | OUTSIDE DIA.<br>(mm) | WALL THICKNESS<br>(mm) | LAY LENGTH<br>(m) | MASS PER<br>PIECE<br>(kg) | TRUCKLOAD LOTS<br>(pcs)* |
|---------------------|----------------------|------------------------|-------------------|---------------------------|--------------------------|
| 300                 | 444.5                | 69.9                   | 2.44              | 550                       | 74                       |
| 375                 | 533.4                | 76.2                   | 2.44              | 746                       | 54                       |
| 450                 | 622.3                | 82.6                   | 2.44              | 930                       | 44                       |
| 525                 | 711.2                | 88.9                   | 2.44              | 1140                      | 35                       |
| 600                 | 800.1                | 95.3                   | 2.44              | 1410                      | 29                       |
| 675                 | 889.0                | 101.6                  | 2.44              | 1680                      | 24                       |
| 750                 | 977.9                | 108.0                  | 2.44              | 1905                      | 21                       |
| 825                 | 1066.8               | 114.3                  | 2.44              | 2225                      | 18                       |
| 900                 | 1155.7               | 120.7                  | 2.44              | 2535                      | 16                       |
| 975                 | 1244.6               | 127.0                  | 2.44              | 2915                      | 14                       |
| 1050                | 1333.5               | 133.4                  | 2.44              | 3115                      | 13                       |
| 1200                | 1511.3               | 146.1                  | 2.44              | 3810                      | 10                       |
| 1350                | 1689.1               | 158.8                  | 2.44              | 4731                      | 8                        |
| 1500                | 1828.8               | 152.4                  | 2.44              | 5180                      | 7                        |
| 1650                | 2006.6               | 165.1                  | 2.44              | 6101                      | 6                        |
| 1800                | 2184.4               | 177.8                  | 2.44              | 6991                      | 5                        |
| 1950                | 2362.2               | 190.5                  | 2.44              | 8110                      | 5                        |
| 2100                | 2540.0               | 203.2                  | 2.44              | 9290                      | 4                        |
| 2250                | 2717.8               | 215.9                  | 2.44              | 10520                     | 3                        |
| 2400                | 2895.6               | 228.6                  | 2.44              | 11880                     | 2                        |
| 2550                | 3073.4               | 241.3                  | 2.44              | 12637                     | 2                        |
| 2700                | 3251.2               | 254.0                  | 2.44              | 14035                     | 2                        |
| 3000                | 3606.8               | 279.4                  | 2.44              | 17185                     | 1                        |

**NOTES:**

- 1) \*SPRING HALF LOAD SEASON WILL AFFECT GROSS WEIGHT.