



***NOTE: MAXIMUM OF (2) OPENINGS PERMITTED**

ALL DIMENSIONS ARE IN mm
DRAWINGS ARE NOT TO SCALE
ALL VIEW AS POURED UNLESS SPECIFIED
WWF SHEETS TO CSA ASTM A1064
WWF Fy = 485MPa (Deformed) 450MPa (Smooth)
REINFORCING TO CSA G.30.18 GRADE 400W

CCP DESIGN REFERENCE: 16-041
MIN. CONC STRENGTH 40MPa
DESIGN ACCORDING TO CSA S6-14
EARTH COVER = 0 - 0.6m
TOLERANCE TO CSA A23.4
MAX OF (2) OPENINGS PERMITTED.
MAX BURIED DEPTH = 4.0m (TO
BOTTOM OF BASE SLAB)

CON CAST PIPE (CCP) STANDARD DRAWING

STD.	-	DOC ID	CX07
SUPER CATCH BASIN 1800 X 900 STACK DRAWING			
0	INITIAL RELEASE	AP	18/OCT/16
REV.	DESCRIPTION	ENG.	DATE
		DRAWN BY	SM
		CHECKED BY	AP/SW
		DATE	18/OCT/2016
		FILE	SuperCB-STACK
		PAGE	1 OF 1